

# #12 Standard Drill Point Roofing Fastener



## Product Description

SHDS #12 Standard Drill Point Roofing Fastener are designed to secure insulation to 16-22 gauge steel and wood decks. The fastener must achieve a penetration depth of 3/4" minimum. The fastener is also available pre-assembled with 3" Galvanized Steel Insulation Plates. Pre-assembled insulation fasteners and plates are fast to install and increase productivity in the mechanical attachment of roof insulation boards.


## Features & Benefits

- Heavier shank and thread diameters than most standard roofing fasteners.
- Buttress thread design provides high pullout resistance.
- Sharp drill point for quick installation.

## Corrosion Resistance

- 1800 hrs salt spray NSS resistance tested by SGS, appearance rating above 10 (ASTM B117-18)
- 15 cycle Kesternich test, no red rust (GB 9789)
- 1500hr salt spray NSS resistance test, no red rust (GB/T 10125)

Length	Thread	PKG(QTY)	Weight
1-5/8"-41mm	Full	1000	13lbs (6.14kg)
2-1/4"-57mm	Full	1000	17lbs (7.99kg)
2-7/8"-72mm	Full	1000	21lbs (9.69kg)
3"-76mm	Full	1000	23lbs (10.40kg)
3-1/4"-83mm	3" (75mm)	1000	24lbs (10.86kg)
3-3/4"-95mm	3" (75mm)	1000	28lbs (12.70kg)
4-1/2"-114mm	3" (75mm)	1000	31lbs (14.29kg)
5"-125mm	3" (75mm)	1000	34lbs (15.55kg)
6"-152mm	4" (102mm)	1000	42lbs (18.96kg)
7"-178mm	4" (102mm)	500	24lbs (11.05kg)
8"-200mm	4" (102mm)	500	28lbs (12.5kg)



Roofing material supplier